


**PRODUCT
DATA
SHEET**



FLAMORT FIRE RETARDANT PAINT

DESCRIPTION:

Flamort Fire Retardant Paint is a Class 'A', water-base, intumescent coating (interior use only). Tested in accordance to ASTM E84 (comparable to UL 723, NFPA 255, and UBC 42-1), this coating complies with many state and local building and fire code requirements. Flamort Paint is a CA. State Approved and Registered Product (Reg.# C-00414). This coating dries to a flat finish and has the appearance of a conventional flat latex paint. When exposed to fire, Flamort Paint puffs up (intumesces) and forms a sponge-like, heat insulating barrier, which protects the underlying substrate.

APPLICATION:

Surface preparation should be carried out according to good painting practices. All dirt, grease, oil, wax, rust and other foreign matter must be removed. When applied to new surfaces, Flamort Paint may be applied with or without a primer. Flamort Paint may be applied to existing paint that is in good condition. Glossy surfaces may require sanding to create a good bond. Wire brush to remove old non-adhering paint. Stir paint well. Apply by brush, roll, or conventional and airless spray methods. Do not apply when surface of air temperatures are below 50 deg. F (10 deg. C). Protect from freezing.

Recommendation for airless application:

Fluid Pressure -	2500 psi
Strainer -	80 mesh
Fluid Hose -	1/4" diameter
Tip -	.021 - .026
Reduction -	up to 7%

CHARACTERISTICS:

Color: White (may be tinted up to 2 fl. oz. per gallon, with Universal Colorants. Check colorant for compatibility)

Spread Rate: 150 sq.ft. in one coat, or 350 sq.ft. in two coats (allow 4 hrs. dry time between coats.)

Volume Solids: 48% +/- 2

Weight Solids: 59% +/- 2

Flash Pt. : None

Reducer/Cleaner: Water

Packaging: 1-gal., 5-gal. pails, and 50 gal. drums

PRECAUTIONS:

Adequate ventilation must be provide during and after application until the coating has dried. Avoid breathing vapors or spray mist. Close container after use. **DO NOT TAKE INTERNALLY.**

KEEP OUR OF REACH OF CHILDREN.
Read MSDS before opening containers.

Flamort Co., Inc. 2368 Alvarado St. San Leandro, CA. 94577
Ph. (510) 357-9494 Fax (510) 351-5427
Email: Info@Flamort.com



Reg. # C-00414